

Polywater®

Prelube 2000™

FIBER OPTIC CABLE BLOWING LUBRICANT



Increases Installation
Distance When Blowing
Fiber Optic Cable



FEATURES AND BENEFITS

- **ULTRA-LOW FRICTION**
Increases blowing distance with ultra-low coating thickness
- **TESTED AND APPROVED**
Endorsed and recommended by most blowing equipment manufacturers for reliable and efficient operation of equipment
- **COMPATIBLE WITH CABLE JACKETS**
Suitable for a variety of cable jackets and ducts including HDPE and PE
- **CLEAN APPLICATION**
Leaves minimal residue and will perform even when dry
- **WINTERGRADE FORMULA**
Version for sub-freezing temperatures available

Blowing Lubricant for Air-Assisted Installation of Fiber Systems

Polywater® Prelube 2000™ is a high-performance lubricant developed for pre-lubricating duct and cable. Its efficient coating thickness reduces frictional drag to increase the speed and continuous distance that cable and innerduct can be installed. Polywater Prelube 2000 is recommended for installation of fiber cable networks and approved by many equipment manufacturers, network owners, contractors and blowing teams.



CATALOG #	PACKAGE DESCRIPTION	UNITS/CASE
P-35 / WP-35	1 qt (0.95 L) Bottle	12
P-128 / WP-128	1 gal (3.8 L) Jug	4
P-640 / WP-640	5 gal (18.9 L) Pail	1

W in the catalog number indicates Winter Grade version.



SPECIFICATIONS AND APPLICATIONS

- **Cable Compatibility:** Passes all compatibility tests for PE jacketed cables.
- **Cost Effectiveness:** Offers significant cost savings over “factory-lubricated” duct.
- **Safe:** Non-hazardous and residue is not combustible.
- **Approved:** Used in networks globally and promoted by equipment manufacturers
- **For More Information, View the [Technical Data Sheet](#)**



polywater.com | +1 651-430-2270

IMPORTANT NOTICE: The statements here are made in good faith based on tests and observations we believe to be reliable. However, the completeness and accuracy of the information is not guaranteed. Before using, the end-user should conduct whatever evaluations are necessary to determine that the product is suitable for the intended use.

American Polywater expressly disclaims any implied warranties and conditions of merchantability and fitness for a particular purpose. American Polywater's only obligation shall be to replace such quantity of the product proven to be defective. Except for the replacement remedy, American Polywater shall not be liable for any loss, injury, or direct, indirect, or consequential damages resulting from a product's use, regardless of the legal theory asserted.

© 2022 American Polywater Corporation LIT-P2000FLYER/REV000

Polywater[®]
Solutions at work.

American Polywater Corporation
11222 60th Street N.
Stillwater, MN 55082 USA

+1 651-430-2270 Main
+31 10 233 0578 Europe, Middle East, N. Africa
email: support@polywater.com